

DISKO FRAMESETS INSTRUCTION & WARRANTY

RETAILER: This framesheet must be provided to the end user.

DISKO is our most versatile and really a “do it all” kind of bike. Weekend bike packing trips, daily commute, winter road rides, and short intense cross race are all the essence of DISKO.

At the core of DISKO is the high quality customized Chromoly tubing built into the well-designed geometry. The front triangle is heat-treated which allows the tube walls to be thinner. The result is reduced weight but without compromising strength. 44mm head tube matches both straight & tapered steer tube fork by simply switching the headset. Press Fit BB30 bottom bracket provides greater power transfer and allows use of single or multiple gears. Superior stopping power is taken care of by our in-house design low mount ISO disc brake dropout. A beautiful curved wishbone seatstay balances the modern functionality into classic steel bike lines.

WARNING: Cycling can be dangerous. Bicycle products should be installed and serviced by a professional mechanic. Never modify your bicycle or accessories. Read and follow all product instructions and warnings including information on the manufacturer’s website. Inspect your bicycle before every ride. Always wear a helmet.

Intended Use: CYCLO-CROSS , CONDITION 2 (Check Owner Manual Appendix A)

This is a set of conditions for the operation of a bicycle that includes paved road surface as well as unpaved and gravel roads and trails with moderate grades. In this set of conditions, contact with irregular terrain and loss of tire contact with the ground may occur. Drops are intended to be limited to 15cm (6") or less.

FRAME COMPATIBILITY

Design Wheel / Tire Size: 27.5 x 1.9"/700 x 42mm w/o fenders, 650b x 48mm/700 x 38mm w/fenders

Rigid Fork Length: 405mm

Fork Offset: 45mm

Headset-Upper: ZS44

Headset-Lower: ZS44

Seatpost: 27.2mm

Bottom Bracket: 68mm Press-fit 30mm

Rear Brake (Rotor) ISO Mount: 160mm

Rear Spacing: 135mm, QR

Bottle Mounts: 2 sets

For complete bike specs and reasoning behind our component choices go to www.velocicycle.com

FORK COMPATIBILITY

Stem Clamp: Ø28.6mm

Crown Race: Ø30mm

Front Brake (Rotor) ISO Mount: 160mm

Spacing: 100mm, QR

Fender Mounts: M5*0.8

Mid-bladed Mounts: M5*0.8

Upper Rack Mounts: M5*0.8

WARNING: do not use rigid forks exceeding 405mm axle-to-crown. Doing so will void the frame warranty and may result in damage or failure of the frame and possible serious injury.

WARNING: Always check for adequate clearance between the front tire and/or fender, and any accessory fitted to the accessory mounts located on the underside of the downtube, through the entire steering range.

Care and Maintenance

Try best to keep your frame clean all time. Dirt & road grimes lead to oxidation and fading of the finish. Dirt will also lead to faster abrasion of the paint. In some extreme cases, this type of abrasion could slightly damage frame material. When your bicycle is not being ridden, store it away from rain, snow, sun, etc. Rain or snow could corrode metal. If your bicycle was exposed to moisture during a ride, dry the bicycle thoroughly before storing it. If water leaks inside the frame, tilt your bicycle to drain the water, or remove the seatpost and turn the bicycle upside down if necessary. If water freezes inside your frame, the expansion of the ice can damage the structure. Remember to clean and lubricate the frame with a frame wax, polish, or protectant before long time storage. Ozone from motors might damage paint, therefore keep your bicycle away from electric motors. Before riding the bicycle again, follow the pre-ride checklist to be sure your bike is in good riding condition.

Inspection

Inspect your frame for signs of fatigue carefully before every ride. Consult with your dealer if any frame part shows signs of fatigue.

WARNING: An improper modification of frame, fork, or component can cause you to lose control and fall.

WARNING: Improper installation of bolts may cause product failure and lead to serious injury.

WARNING: Racks or fenders with Incompatible clamping devices might damage bicycle fork, causing a loss of control. Consult your dealer if you are not sure whether the device is compatible.

Limited Warranty

VELOCI CYCLE warrants the repair or replacement of original VELOCI CYCLE products due to defects in material and/or workmanship according to the following conditions:

Duration of warranty:

Frame: 3 years, Fork: 2 years, Paint & Decals: 1 year. Save your dated receipt for proof of purchase.

This warranty doesn't cover the following:

- Normal wear and tear (as with bicycles, riding will cause certain deterioration)
- Improper assembling (ask your local bike shop for help, if you are not a skilled mechanic)
- Inappropriate follow-up maintenance
- Installation of components, parts or accessories not originally intended for or compatible with the bicycle as sold
- Damage or failure caused by accident, misuse, abuse or neglect
- Labor charges for part replacement or changeover

This warranty applies only to products purchased through an authorized dealer or distributor and is not transferable. Claims must be sent through an authorized dealer/distributor. In no event shall VELOCI be liable for any loss, inconvenience or damage, whether direct, incidental, consequential, or otherwise resulting from breach of any express or implied warranty or condition, of merchantability, fitness for a particular purpose, or otherwise with respect to our products except as set forth herein

Warranty Process

If you are facing a warranty case and not sure whether the issue is covered, please always first contact the shop you purchased our products. If the shop can't or doesn't know how to do, you can contact the distributor or get the shop to do so. If all of the above doesn't work, welcome to contact us.

Providing more relevant information will help accelerate the whole process. Please describe how the damage happened or when you started to notice the problem.

Sending us meaningful and clear images of the problem will be also helpful. Thanks for understanding.

Contact Us

Questions, comments and build images can be and should be directed to:

VELOCI CYCLE

Rm.13, 11F., Sec.1, Zhongxiao W.Rd., Zhongzheng Dist.

Taipei City 10041, Taiwan (R.O.C.)

Phone: +886-2-23146545

Web: www.velocicycle.com

E-mail: velocicycle@gmail.com